

DIMM DDR PC-3200 400 MHz



Features


- ▶ Fully PC-3200 Compliant (DDR400)
- ▶ Backward compatible with
PC2700 (DDR 333)
PC2100 (DDR 266)
- ▶ JEDEC-Standard 184-pin Dual
Inline Memory Module (DIMM)
- ▶ Unbuffered
- ▶ Cas Latency 3
- ▶ Power Supply: 2.5V \pm 0.2V
- ▶ 64ms, 8k refresh
- ▶ Serial Presence Detect (SPD)
- ▶ Pure Power and Ground Planes
- ▶ Gold PCB connector



Ordering Information

	DENSITY	REFERENCE	EAN
Optima	512MB	DIMM10512N/3200-BX	3536401460244
Optima	1GB	DIMM101GBN/3200-BX	3536401460428
Premium	512MB	D512N08T400Q-SB	3536401461791
Premium	1GB	D1GBN16T400Q-SB	3536401461807

All of our capacities are also available in Premium packagings for distribution and integration purposes.



Optima
packaging



Premium
packaging

Not sure of your
memory needs ?

Try our online
configurator !

PNY.EU



Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

For more information, visit : **WWW.PNY.EU**